



- **12-YEAR LIMITED TANK AND PARTS WARRANTY**
1-YEAR LABOR WARRANTY
- Cobalt Blue Ultra Coat™ glass-lined tank with two large anode rods for superior internal tank protection.
- **3" ENERGY EFFICIENT FOAM INSULATION (R-Value 24.0).**
(30 Gallon, 2 1/2" of Foam Insulation, R-Value 20.0).
- TWO ELEMENTS: The lower handles normal needs while the upper responds to heavy demands.
- SUPER LIMEGUARD™ ELEMENTS: Last longer; superior resistance to lime buildup.
- DUALWATT™ LOWER ELEMENT: EASILY CONVERTS FROM 3800 WATT TO 5500 WATT - FITS THE CUSTOMER'S WIRING!
- Self-Cleaning RotoSwirl™ cold water inlet tube - helps maintain efficiency by swirling water to help prevent mineral buildup in tank.
- FACTORY-INSTALLED TEMPERATURE AND PRESSURE RELIEF VALVE.
- Meets energy efficiency requirements of Federal NAECA and all state laws for replacement water heaters.

NOTE: Bold type indicates additional features and benefits over the Kenmore® 9 Series.

Kenmore® 12-Year Electric



Factory set for 3800 watt operation, requires a minimum 12 gauge wire and 20 amp fusing. Provides 17.3 gallons per hour of recovery at a 90° temperature rise. With parts and instructions included, the lower element converts to 5500 watt operation which requires 10 gauge wire and 30 amp fusing. 5500 watt element operation provides 25.0 gallons per hour of recovery at a 90° temperature rise.

Item #	1st Hour Rating	Annual Cost of Operation	Energy Factor	Recovery At 90° Rise	Gallon Size	Wattage At 240V	Minimum Fuse Required	Minimum Wire Size	Dimensions		R-Value
									Diameter	Height	
32134	44 Gal 47 Gal	\$492	.95	17.3 GPH 25.0 GPH	30	3800 W 5500 W	20 AMP 30 AMP	12 GA. 10 GA.	19"	47"	20.00
32144	53 Gal 57 Gal	\$492	.95	17.3 GPH 25.0 GPH	40	3800 W 5500 W	20 AMP 30 AMP	12 GA. 10 GA.	20"	60 1/2"	24.00
32154	64 Gal 67 Gal	\$492	.95	17.3 GPH 25.0 GPH	55	3800 W 5500 W	20 AMP 30 AMP	12 GA. 10 GA.	22 1/2"	62"	24.00
32164	69 Gal 71 Gal	\$492	.95	17.3 GPH 25.0 GPH	66	3800 W 5500 W	20 AMP 30 AMP	12 GA. 10 GA.	24"	62"	24.00
32184	78 Gal 81 Gal	\$492	.95	17.3 GPH 25.0 GPH	80	3800 W 5500 W	20 AMP 30 AMP	12 GA. 10 GA.	26"	62"	24.00

150 PSI working pressure

Water Connections: Top Plumbed 3/4" NPT